

BWE-Standard-Element

**BWE
BAU**

Satteldachbinder 3 % I, Spannbeton C 35/45 - C50/60

Typ	Querschnittsfläche im First (m ²)	zul. q ohne Eigengew. (KN/m)	max. d	b _o	b	b _u	d _o	s _o	a	s _u	d _u
$L \leq 20.00 \text{ m}$											
S 111	0.2061	16.3	111	40	11	27	15.3	4.7	66.5	8	16.5
S 112	0.2283	16.3	111	42	13	29	15.3	4.7	66.5	8	16.5
$20.00 \text{ m} < L \leq 25.00 \text{ m}$											
S 117	0.2355	11.4	117.5	60	11	27	11	8	74	8	16.5
S 116	0.2590	11.4	117.5	62	13	29	11	8	74	8	16.5
S 118	0.2143	11.4	118.5	40	11	27	15.3	4.7	74	8	16.5
S 119	0.2380	11.4	118.5	42	13	29	15.3	4.7	74	8	16.5
$25.00 \text{ m} < L \leq 30.00 \text{ m}$											
S 125	0.2438	8.5	125	60	11	27	11	8	81.5	8	16.5
S 126	0.2688	8.5	125	62	13	29	11	8	81.5	8	16.5
– S 112, S 116, S 119 und S 126 haben Betondeckung für Außenbauteile – Alle Bindertypen erfüllen F90											

BWE-BAU
Fertigteilwerk GmbH
 Postfach 1260
 26002 Oldenburg

Tel +49 441 6804-0
 Fax +49 441 6804-120
 E-mail info@bwe-bau.de